










Specifications and Ordering Information for 3M Cable Ties

Product Description	Product Number	UPC (054007-)	Approx. Length	Approx. Max. Bundle Dia.	Approx. Width	Approx. Thickness	Loop Tensile	Inner Unit Pack	Certifications and Listings
Miniature Cable Ties									
									
Natural	06224	06224	4" (102 mm)	0.8" (20 mm)	0.1" (2.5 mm)	0.04" (1.0 mm)	18 lbs. (80 N)	100/bag	UL
	06248	06248						1000/bag	
Weather-Resistant Black	06200	06200	4" (102 mm)	0.8" (20 mm)	0.1" (2.5 mm)	0.04" (1.0 mm)	18 lbs. (80 N)	100/bag	UL
	06270	06270						1000/bag	
Intermediate Cable Ties									
									
Natural	06225	06225	6" (152 mm)	1.25" (32 mm)	0.14" (3.6 mm)	0.04" (1.0 mm)	30 lbs. (133 N)	100/bag	UL
	06249	06249						1000/bag	
Weather-Resistant Black	06201	06201	6" (152 mm)	1.25" (32 mm)	0.14" (3.6 mm)	0.04" (1.0 mm)	30 lbs. (133 N)	100/bag	UL
	06271	06271						1000/bag	
Standard Cable Ties									
									
Natural	06226	06226	8" (203 mm)	1.75" (44 mm)	0.18" (4.6 mm)	0.05" (1.3 mm)	50 lbs. (222 N)	100/bag	UL
	06250	06250						1000/bag	
Natural	06227	06227	12" (305 mm)	3" (76 mm)	0.18" (4.6 mm)	0.05" (1.3 mm)	50 lbs. (222 N)	100/bag	UL
	06251	06251						1000/bag	
Natural	06228	06228	15" (381 mm)	4" (102 mm)	0.18" (4.6 mm)	0.05" (1.3 mm)	50 lbs. (222 N)	50/bag	UL
	06252	06252						500/bag	
Weather-Resistant Black	06202	06202	8" (203 mm)	1.75" (44 mm)	0.18" (4.6 mm)	0.05" (1.3 mm)	50 lbs. (222 N)	100/bag	UL
	06272	06272						1000/bag	
Weather-Resistant Black	06203	06203	12" (305 mm)	3" (76 mm)	0.18" (4.6 mm)	0.05" (1.3 mm)	50 lbs. (222 N)	100/bag	UL
	06273	06273						1000/bag	
Weather-Resistant Black	06204	06204	15" (381 mm)	4" (102 mm)	0.18" (4.6 mm)	0.05" (1.3 mm)	50 lbs. (222 N)	50/bag	UL
	06274	06274						500/bag	
Heavy Duty Cable Ties									
									
Natural	06229	06229	8" (203 mm)	2" (51 mm)	0.30" (7.6 mm)	0.07" (1.8 mm)	120 lbs. (533 N)	50/bag	UL
Natural	06240	06240	15" (381 mm)	4" (102 mm)	0.30" (7.6 mm)	0.07" (1.8 mm)	120 lbs. (533 N)	50/bag	UL
	06264	06264						500/bag	
Natural	06247	06247	33" (838 mm)	9.75" (248 mm)	0.30" (7.6 mm)	0.09" (2.3 mm)	175 lbs. (777 N)	50/bag	UL
Weather-Resistant Black	06206	06206	8" (203 mm)	2" (51 mm)	0.30" (7.6 mm)	0.07" (1.8 mm)	120 lbs. (533 N)	50/bag	UL
	06207	06207						50/bag	
Weather-Resistant Black	06207	06207	15" (381 mm)	4" (102 mm)	0.30" (7.6 mm)	0.07" (1.8 mm)	120 lbs. (533 N)	50/bag	UL
	06277	06277						500/bag	
Weather-Resistant Black	06246	06246	33" (838 mm)	9.75" (248 mm)	0.34" (8.6 mm)	0.09" (2.3 mm)	175 lbs. (777 N)	50/bag	UL

Specifications and Ordering Information for 3M™ Cable Ties (continued)

Product Description	Product Number	UPC (054007-)	Approx. Length	Approx. Max. Bundle Dia.	Approx. Width	Approx. Thickness	Loop Tensile	Inner Unit Pack	Certifications and Listings
Extra Heavy Duty Cable Ties									
Natural	06260	06260	36" (914 mm)	11" (279 mm)	0.34" (8,6 mm)	0.09" (2,3 mm)	175 lbs. (777 N)	50/bag	UL
Weather-Resistant Black	06259	06259	36" (914 mm)	11" (279 mm)	0.34" (8,6 mm)	0.09" (2,3 mm)	175 lbs. (777 N)	50/bag	UL
Mounting Cable Ties, Standard (#10 Screw)									
Natural	06232	06232	8" (203 mm)	1.75" (44 mm)	0.19" (4,8 mm)	0.06" (1,5 mm)	50 lbs. (222 N)	100/bag	UL
	06256	06256					1000/bag		
Natural	06234	06234	15" (381 mm)	4" (102 mm)	0.19" (4,8 mm)	0.06" (1,5 mm)	50 lbs. (222 N)	50/bag	UL
	06258	06258					500/bag		
Weather-Resistant Black	06205	06205	8" (203 mm)	1.75" (44 mm)	0.19" (4,8 mm)	0.06" (1,5 mm)	50 lbs. (222 N)	100/bag	UL
	06275	06275					1000/bag		
Mounting Cable Ties, Heavy Duty (1/4" Screw)									
Natural	06243	06243	15" (381 mm)	4" (102 mm)	0.30" (7,6 mm)	0.07" (1,8 mm)	120 lbs. (533 N)	50/bag	UL
	06267	06267					500/bag		
Double Loop Cable Ties, Standard									
Natural	06242	06242	15" (381 mm)	4" (102 mm)	0.18" (4,6 mm)	0.05" (1,3 mm)	50 lbs. (222 N)	50/bag	UL
	06266	06266					500/bag		
Double Loop Cable Ties, Heavy Duty									
Natural	06245	06245	15" (381 mm)	4" (102 mm)	0.30" (7,6 mm)	0.07" (1,8 mm)	120 lbs. (533 N)	50/bag	UL
	06269	06269					500/bag		

Continued on next page