



# Polyester Tape (Pink)

## 335

### Technical Data

**Product Description** A polyester tape with a very low tack adhesive system for use as a protective tape.

Product Construction	Backing	Adhesive	Color
	Polyester Film	Rubber	Pink

**Typical Physical Properties** **Note:** The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

		ASTM Test Method
Adhesion to Steel:	2 oz./in. width (2 N/100mm)	D-3330
Tensile Strength at Break:	24 lbs./in. width (420 N/100mm)	D-3759
Elongation at Break:	125%	D-3759
Backing Thickness:	.9 mils (.02mm)	D-3652
Total Tape Thickness:	1.6 mils (.04mm)	D-3652

- General Information**
- In general, protective tapes help to protect polished metal and plastic surfaces with minimum adhesion build-up and clean removal. This performance is enhanced by clean surfaces prior to application. However, the following use information should be noted.
  - Adhesion levels can increase from any of the following conditions:
    - Extended exposure to direct sunlight
    - High stacking pressures
    - Extended application to copper bearing surfaces

**Shelf Life** To obtain best performance, use this product within 12 months from date of manufacture and store under normal conditions of 60° to 80°F (16° to 27°C) and 40 to 60% R.H. in the original carton.

- Application Ideas**
- Protection from fumes and splash during plating processes on the upper portion of printed wiring boards. Polyester Tape 335 has a lower adhesive tack level than 3M™ Fume Protection Tape 1290 which can also be used for this application.
  - Protection of polished stainless steel and aluminum in fabrication, shipping and storage.
  - Protection of nameplates and instrument panels during shipping and installation.
  - Protection of non-image side of inner layers of multilayer printed wiring boards.

Features	Features	Advantages	Benefits
	Low tack adhesive	Easy removal	Helps reduce labor cost
	Transparent backing	Allows visual inspection without tape removal	Helps save money on rework
	Elastic backing	Withstands most forming operations	Helps save money on rework
	Abrasion resistant backing	Resists tearing during forming	Helps reduce labor costs

**Technical Information and Data** The technical information and data, recommendations, and other statements provided in this document are based on tests or experience which 3M believes to be reliable, but the accuracy or completeness of such information is not guaranteed.

**Product Use** Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be used with the 3M product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user’s knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user’s method of application.

**Limited Warranty and Limited Remedy** The 3M product will be free from defects in material and manufacture for a period of one (1) year from the date of manufacture. 3M MAKES NO OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user’s method of application. If the 3M product is defective within the warranty period stated above, YOUR EXCLUSIVE REMEDY AND 3M’S SOLE OBLIGATION SHALL BE, AT 3M’S OPTION, TO REPLACE OR REPAIR THE 3M PRODUCT OR REFUND THE PURCHASE PRICE OF THE 3M PRODUCT.

**Limitation of Liability** Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, warranty, negligence, or strict liability.



This Industrial Tape and Specialties Division product was manufactured under a 3M quality system registered to ISO 9002 standards.



**Industrial Tape and Specialties Division**

3M Center, Building 220-7W-03  
 St. Paul, MN 55144-1000  
 1 800 362 3550  
 1 800 223 7427 Fax on Demand  
 www.3M.com/industrialtape

© 3M IPC 2001  
 All rights reserved.

70-0703-2509-0  
 September/1/1999