



# Circuit Plating Tape

1279

Technical Data

July, 1995

**Product Description** A polyester film with special blended adhesive for masking many printed wiring boards during the gold tip plating process.

Construction	Backing	Adhesive	Color	Standard Roll Length
	Polyester	Silicone/Rubber Blend	Orange	144 yds. (132 m) and 72 yds. (65 m)

**Typical Physical Properties and Performance Characteristics** **Note: The following technical information and data should be considered representative or typical only and should not be used for specification purposes.**

		ASTM Test Method
Adhesion to Steel:	31 oz./in. width (33.9 N/100 mm)	D-3330
Tensile Strength: (Break or Yield)	28 lbs./in. width (490.3 N/100 mm)	D-3759
Elongation: (Break or Yield)	122%	D-3759
Backing Thickness:	.8 mil (.020 mm)	D-3652
Total Tape Thickness:	3.8 mils (.096 mm)	D-3652

- General Information**
- Low stretch polyester film for machine, as well as hand application.
  - Tape must be firmly pressed down by equipment with rubber covered rollers. Hand rolling usually does not provide enough pressure. A vivid outline of the circuit leads usually indicate adequate pressure was used.
  - Solvent clean-up of the board is recommended to facilitate subsequent soldering.
- Note:** Be sure to follow the manufacturer's precautions and directions for use when using solvents.
- Shelf life – important to rotate inventory.

- Application Ideas**
- Masking of many printed wiring boards during solder stripping and precious metal plating of fingers.

# Circuit Plating Tape

1279

Features	Advantages	Benefits
<ul style="list-style-type: none"><li>• Polyester backing</li></ul>	<ul style="list-style-type: none"><li>• Reduces stretch and recovery of tape and associated uneven stop-off line</li></ul>	<ul style="list-style-type: none"><li>• Helps save money by reducing number of reject boards</li></ul>
<ul style="list-style-type: none"><li>• Thick adhesive coating</li></ul>	<ul style="list-style-type: none"><li>• Reduces undercutting because adhesive helps block out solutions between fingers</li></ul>	<ul style="list-style-type: none"><li>• Helps save money by reducing reject boards</li></ul>
<ul style="list-style-type: none"><li>• Specially designed adhesive</li></ul>	<ul style="list-style-type: none"><li>• Tape generally performs better when no heat is used to apply tape</li><li>• Reduces adhesive transfer to printed wiring boards</li></ul>	<ul style="list-style-type: none"><li>• Helps save energy and labor costs</li><li>• Helps save money by reducing clean-up time</li></ul>

## For Additional Information

To request additional product information or to arrange for sales assistance, call 612-733-1441. Address correspondence to: 3M Industrial Tape and Specialties Division, 3M Center, Building 220-8E-04, St. Paul, MN 55144-1000. Our fax number is 612-733-9175. In Canada, phone: 1-519-451-2500. In Puerto Rico, phone: 1-809-750-3000. In Mexico, phone: 5-728-0400.

## Important Notice

3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of application. Please remember that many factors can affect the use and performance of a 3M ITSD product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M ITSD product. Given the variety of factors that can affect the use and performance of a 3M ITSD product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M ITSD product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

## Limitation of Remedies and Liability

If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including negligence, warranty, or strict liability.

ISO 9002

This Industrial Tape and Specialties Division product was manufactured under a 3M quality system registered to ISO 9002 standards.

# 3M

Industrial Tape and Specialties Division

3M Center, Building 220-7E-01  
St. Paul, MN 55144-1000



Recycled Paper  
40% pre-consumer  
10% post-consumer

Printed in U.S.A.  
©3M 1994 70-0703-2517-3